



Model	Amps (120VAC)				Amps (240VAC)				A	B	C	D	E	Hangin g
	-NL	-RL	-ETN-NL	-ETN-RL	-NL	-RL	-ETN-NL	-ETN-RL						
2700	0.83	0.90	1.05	N/A	0.42	0.45	0.53	N/A	3'	8'	8"	30"	6"	62 lbs.
2740	1.08	1.19	1.40	N/A	0.54	0.60	0.70	N/A	4'	12'	16"	48"	6"	118 lbs.
4707	1.57	1.74	1.89	1.95	0.79	0.88	0.95	0.98	4'	18'	52"	84 1/2"	50"	185 lbs.
4720	1.10	1.22	1.31	1.37	0.55	0.62	0.66	0.69	3'	16'	56"	78"	54"	136 lbs.
4721	1.30	1.47	1.52	1.62	0.66	0.74	0.08	0.82	3'	16'	56"	78"	54"	148 lbs.
4725	1.20	1.37	1.41	1.52	0.06	0.69	0.71	0.76	3'	16'	56"	78"	54"	140 lbs.
4755	0.80	0.87	1.02	N/A	0.40	0.43	0.51	N/A	3'	8'	8"	30"	6"	65 lbs.
4765	0.24	0.35	0.45	0.5	0.12	0.18	0.23	0.25	3'	5'	9"	30"	6"	40 lbs.
9710	0.53	0.56	N/A	N/A	0.27	0.28	N/A	N/A	3'	5'	9"	20 1/2"	6"	40 lbs.

- Notes:**
1. Lifting Point 3/8"-16 Eyebolts can be threaded into the lifting point to lift the scoreboard for mounting or for suspension mount. Eyebolts can be removed after the scoreboard is mounted.
 2. Mount Scoreboard securely using 3/8" bolts or anchors and supplied washers using the existing mounting holes or drill 1/2" alternate locations.
 3. This sign is intended to be installed in accordance with the requirements of Article 600 of the Nationale Electric Code and/or other applicable codes. This includes proper grounding and bonding of the sign.

Single Section Indoor LED Scoreboard Installation			Nevco, Inc. Greenville, Illinois 62246	
			Drawing No. 241-0283	
	Last ECO	Drawn HW	Date 4/11/13	Sheet 1 of 1