



Signal Connections

Model	Amps (120VAC)				Amps (240VAC)				A	B		C		D	E	F	G	Hanging Weight
	-NL	-RL	-ETN-NL	-ETN-RL	-NL	-RL	-ETN-NL	-ETN-RL		w/ 8'	w/ 12'	w/ 8'	w/ 12'					
SD7-5	0.7	0.8	0.8	0.7	0.4	0.4	0.4	0.4	12 1/2	65 1/2	84 1/2	144 1/2	129 1/2	72	36	9	6	110 lbs.
SD7-9	1.2	1.3	1.3	1.2	0.6	0.7	0.7	0.6	20 1/2	89 1/2	108 1/2	176 1/2	224 1/2	96	60	9	6	230 lbs.
PTF7	0.9	1.0	1.0	0.9	0.5	0.5	0.5	0.5	20 1/2	89 1/2	108 1/2	176 1/2	224 1/2	80 1/2	60	9	6	60 lbs.
F712	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	9 7/8	50 1/4	89 1/4	126 5/8	174 5/8	80 1/2	20 3/4	2	3	22 lbs.
F715	0.3	0.3	0.3	0.3	0.1	0.1	0.1	0.1	9 7/8	50 1/4	89 1/4	126 5/8	174 5/8	97 1/2	20 3/4	2	3	22 lbs.

Notes:

1. Lifting Point 3/8"-16 Eyebolts can be threaded into the lifting point to lift the scoreboard for mounting or for suspension mount. Eyebolts can be removed after the scoreboard is mounted.
2. Mount Scoreboard securely using 3/8" bolts or anchors using the existing mounting holes or drill 1/2" alternate locations.
3. This sign is intended to be installed in accordance with the requirements of Article 600 of the Nationale Electric Code and/or other applicable codes. This includes proper grounding and bonding of the sign.
4. Connect Coax from control point or receiver to Home input, then daisy chain supplied coax cable from output to Guest input. For convenience, Guest may be connected first by connecting to Guest input and going from output to Home input. See "Signal Connections"

SD7, PTF7, and F7 Installation		<p><b>NEVCO</b></p> <p>Nevco, Inc. Greenville, Illinois 62246</p>
Last ECO		
Drawn <b>DLP</b>	Date <b>4/12/13</b>	Sheet <b>1 of 1</b>