



# MODEL 1603



**Size:** 36' x 9' x 8" (10.97 x 2.74 x .20 meters)

**Approximate hanging weight:** 930 lbs. (422 kg) **With ETNs:** 992 lbs. (450 kg)

**Digit Size:** 18"/24" **Digit Color:** High Intensity Red, Amber, or Translucent White

AT BAT 49	BALL 3	STRIKE 2	OUT 2	H 8	E 0								
GUESTS	1	2	3	4	5	6	7	8	9	10	RUNS 2	HITS 3	ERRORS 1
HOME	0	0	3	0	0	0	0	0	0	0	3	8	0

AT BAT 49	BALL 3	STRIKE 2	OUT 2	H 8	E 0								
BEARS	1	2	3	4	5	6	7	8	9	10	RUNS 2	HITS 3	ERRORS 1
EAGLES	0	0	3	0	0	0	0	0	0	0	3	8	0

SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

AT BAT 49	BALL 3	STRIKE 2	OUT 2	H 8	E 0								
GUESTS	1	2	3	4	5	6	7	8	9	10	RUNS 2	HITS 3	ERRORS 1
HOME	0	0	3	0	0	0	0	0	0	0	3	8	0

SHOWN WITH OPTIONAL WHITE LEDS

## Nevco's largest inning-by-inning scoreboard designed for combination Baseball/Softball facilities.

- Designed to withstand wind load speed zones exceeding 150 mph.
- Operate wired or wireless.
- Electronic Team Names (ETNs) available in place of Home and Guest caption plates.
- Includes Hit and Error Indicators.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Flush sign mounting.

\*Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

[WWW.NEVCO.COM](http://WWW.NEVCO.COM)

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: [INFO@NEVCO.COM](mailto:INFO@NEVCO.COM)

# INTEGRATED DISPLAY AND SCORING SOLUTIONS




## Model 1603 (Outdoor) Baseball/Softball Scoreboard

### SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 1603	MPC(W)-4/5/6	MPCW WIRELESS	MPCX <sub>2</sub> WIRELESS
<b>LINE SCORES</b> 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9 for ten (10) innings.	Displays 0-9 for ten (10) innings.	Displays 0-9 for ten (10) innings.
<b>RUNS</b> 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99. Total runs accumulate for up to 30 innings as each inning score is entered.	Displays 0-99. Total runs accumulate for up to 30 innings as each inning score is entered.	Displays 0-99. Total runs accumulate for up to 19 innings as each inning score is entered.
<b>HITS</b> 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99.	Displays 0-99.	Displays 0-99.
<b>ERRORS</b> 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9.	Displays 0-9.	Displays 0-9.
<b>AT BAT</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99.	Displays 0-99.	Displays 0-99.
<b>BALL</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9.	Displays Blank-9.	Displays Blank-9.
<b>STRIKE</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9.	Displays Blank-9.	Displays Blank-9.
<b>OUT</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9.	Displays Blank-9.	Displays Blank-9.
<b>H O R E</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays the letter H for hit or the letter E for error.	Displays the letter H for hit or the letter E for error.	Displays the letter H for hit or the letter E for error.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



**AGENCY APPROVAL:** UL/CUL listed, FCC, CE, INDUSTRY CANADA.

**SCOREBOARD:** Size 36"L x 9'H x 8"D (10.97 x 2.72 x .20 meters), constructed of aluminum. Scoreboard has 2" white outline striping. Hanging weight approximately 930 lbs. (422 kg) or 992 lbs. (450 kg) with ETNs.

**CAPTIONS:** HOME, GUESTS, AT BAT, BALL STRIKE, OUT, H, E, white letters 15" high. All other captions white letters 10" high. (HOME and GUESTS are omitted when ordered with ETNs.)

**LED UNITS:** Seven-bar segmented digits with protective aluminum cover.

**BUILT-IN LIGHTNING PROTECTION:** All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

**POWER WITH ETNS (RED/AMBER):** 120 VAC, 6.2 Amps, 50/60 Hz. / 240 VAC, 3.1 Amps, 50/60 Hz. Requires earth ground.

**POWER WITHOUT ETNS (RED/AMBER):** 120 VAC, 5.0 Amps, 50/60 Hz. / 240 VAC, 2.5 Amps, 50/60 Hz. Requires earth ground.

**POWER WITH ETNS (TRANSLUCENT WHITE):** 120 VAC, 9.5 Amps, 50/60 Hz. / 240 VAC, 4.8 Amps, 50/60 Hz. Requires earth ground.

**POWER WITHOUT ETNS (TRANSLUCENT WHITE):** 120 VAC, 8.5 Amps, 50/60 Hz. / 240 VAC, 4.2 Amps, 50/60 Hz. Requires earth ground.

**GUARANTEE:** TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: [NEVCO.COM/WARRANTY-LIMITATION/](http://NEVCO.COM/WARRANTY-LIMITATION/)

**U.S. SERVICE: 1-800-851-4040**

**INTERNATIONAL SERVICE: 1-618-664-0360**

**CANADA SERVICE: 1-800-461-8550**



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

[WWW.NEVCO.COM](http://WWW.NEVCO.COM)

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: [INFO@NEVCO.COM](mailto:INFO@NEVCO.COM)