



OUTDOOR MULTI-SPORT

SCOREBOARDS

MODEL 3680



Size: 18' x 8' x 8" (5.49 x 2.44 x .20 meters)


Approximate hanging weight: 420 lbs. (191 kg) **with ETNs:** 590 lbs. (268 kg)

Digit Size: 24" **Digit Color:** High Intensity Red or Amber



NEW *Intelligent Captions™*
CHANGE AUTOMATICALLY
between sports!

- FOOTBALL
- SOCCER
- LACROSSE
- BASEBALL
- SOFTBALL
- FIELD HOCKEY



Advanced timing features ideal for combination Baseball, Softball, Football, Soccer, Lacrosse and Field Hockey facilities.

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Large digits easily seen from long distances.
- Designed to withstand wind load speed zones exceeding 150 mph.
- Includes Time Outs Left and built-in Horn.
- White outline striping separates features for greatest readability.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- Flexible mounting. Can mount directly to columns OR on laterals for complex or retro-fit installation.



ELECTRONIC TEAM NAMES
COME STANDARD WITH
INTELLIGENT CAPTION
SCOREBOARDS!

Combine your scoreboard with a Nevco monochrome or full-color message center to create a complete scoring and display system. Team/Sponsor signs also available.



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:
WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS




Model 3680 (Outdoor) Multi-Sport Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 3680	MPC(W)-4/5/6	MPCW-7	MPCX ₂ WIRELESS
TIMING 24" High Intensity Red or Amber LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.
TEAM SCORES 24" High Intensity Red or Amber LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
INNING 18" High Intensity Red or Amber LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
AT BAT 24" High Intensity Red or Amber LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
BALL 24" High Intensity Red or Amber LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
STRIKE 24" High Intensity Red or Amber LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
OUT 24" High Intensity Red or Amber LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
TIME OF DAY	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	N/A
HORN	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	N/A
JUNCTION BOX	One (1) 4" x 2 1/8" x 2 1/8" with cover, to be installed in dry location (press box), furnished.	N/A	N/A
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) 3/4" diameter. Order length required.	N/A	N/A
SEGMENT TIMING	Supported.	Supported.	Requires MPCX ₂ segment timer control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 18"L x 8"H x 8"D (5.49 x 2.44 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Four (4) brackets provided for mounting. Hanging weight approximately 420 lbs. (191 kg) with ETNs: 590 lbs. (268 kg).

INTELLIGENT CAPTIONS: (2) 8x48, (4) 8x32, (2) 8x16.

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

POWER: 120 VAC, 6.3 Amps, 50/60 Hz. / 240 VAC, 3.2 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: WWW.NEVCO.COM/INFO/GUARANTEE.PHP

U.S. SERVICE: 1-800-851-4040. **INTERNATIONAL SERVICE:** 1-618-664-0360. **CANADA SERVICE:** 1-800-461-8550.

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM



MAXIMIZE YOUR IMPACT®