



MODEL 3656

Size: 18' x 8' x 8" (5.49 x 2.44 x .20 m)

Approximate hanging weight: 420 lbs. (191 kg) with ETNs: 482 lbs. (219 kg)

Digit Size: 24"/18" Digit Color: High Intensity Red, Amber, or Translucent White



SHOWN WITH OPTIONAL WHITE LEDS



SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

Advanced timing features ideal for combination Football, Baseball, Soccer, Lacrosse and Field Hockey facilities.

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Includes Time Outs Lefts and built-in Horn.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- Flush sign mounting.

* Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS




Model 3656 (Outdoor) Football/Baseball/Soccer/Lacrosse/Field Hockey Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 3656	MPCW-7	MPCX ₂ WIRELESS
TIMING 24" High Intensity Red, Amber, or Translucent White LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.
TEAM SCORES 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99
QUARTER 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9
BALL ON 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99
DOWN 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9
YDS TO GO 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99
TIME OUTS LEFT 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9
HORN	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.
SEGMENT TIMING	Supported.	MPCX ₂ Segment Timer control required.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 18'L x 8'H x 8"D (5.49 x 2.44 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Hanging weight approximately 420 lbs. (191 kg) with ETNs: 482 lbs. (219 kg).

CAPTIONS: HOME, GUESTS, DOWN, TO GO, QTR, BALL ON white 15" high. TOL (2) white 6" high. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 3.2 Amps, 50/60 Hz. / 240 VAC, 1.6 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (RED/AMBER): 120 VAC, 4.4 Amps, 50/60 Hz. / 240 VAC, 2.2 Amps, 50/60 Hz. Requires earth ground.

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 5.4 Amps, 50/60 Hz. / 240 VAC, 2.7 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 6.5 Amps, 50/60 Hz. / 240 VAC, 3.2 Amps, 50/60 Hz. Requires earth ground.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION/

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM



MAXIMIZE YOUR IMPACT®