



FOOTBALL

SCOREBOARDS



MODEL 3658

Size: 16' x 5' x 8" (4.88 x 1.52 x .20 meters)

Approximate hanging weight: 260 lbs. (118 kg) **with ETNs:** 315 lbs. (143 kg)

Digit Size: 18" **Digit Color:** High Intensity Red, Amber, or Translucent White



SHOWN WITH OPTIONAL WHITE LEDS



SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

Advanced timing features ideal for combination Football, Soccer, Lacrosse and Field Hockey facilities.

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Includes built-in Horn.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.

* **Translucent White LEDs cannot be intermixed with other digit color on one scoreboard**



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS




Model 3658 (Outdoor) Football Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

| MODEL 3658 | MPCW-7 | MPCX ₂ WIRELESS |
|--|---|---|
| TIMING 18" High Intensity Red, Amber, or Translucent White LED Digits | Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute. | Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute. |
| TEAM SCORES 18" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-99 | Displays 0-99 |
| QUARTER 18" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-9 | Displays 0-9 |
| YDS TO GO 18" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-99 | Displays 0-99 |
| DOWN 18" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-9 | Displays 0-9 |
| TIME OF DAY | In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". | N/A |
| HORN | Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time. | Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time. |
| JUNCTION BOX | N/A | N/A |
| CONTROL CABLE | N/A | N/A |
| SEGMENT TIMING | Supported. | Requires MPCX ₂ segment timer control. |

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 16'L x 5'H x 8"D (4.88 x 1.52 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Six (6) brackets provided for mounting. Hanging weight approximately 260 lbs. (118 kg) with ETNs: 315 lbs. (143 kg).

CAPTIONS: HOME, GUESTS, DOWN, YDS TO GO, QTR, white 10" high. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 1.6 Amps, 50/60 Hz. / 240 VAC, 0.8 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (RED/AMBER): 120 VAC, 2.6 Amps, 50/60 Hz. / 240 VAC, 1.3 Amps, 50/60 Hz. Requires earth ground.

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 2.7 Amps, 50/60 Hz. / 240 VAC, 1.3 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 3.6 Amps, 50/60 Hz. / 240 VAC, 1.8 Amps, 50/60 Hz. Requires earth ground.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION/

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM