





MODEL 7615


Size: 24' x 10' 6" x 8" (7.32 x 3.20 x .20 meters)

Approximate hanging weight: 730 lbs. (331 kg) **with ETNs:** 792 lbs. (359 kg)

Digit Size: 24" **Digit Color:** High Intensity Red, Amber, or Translucent White



SHOWN WITH OPTIONAL WHITE LEDES



SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

Advanced timing features ideal for combination Football, Baseball, Softball, Soccer, Lacrosse, Field Hockey and Track facilities.

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Includes Possession Indicators and built-in Horn.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- When operating as a track board, the 1/100th of a second displays.
- All 7600 Series models are compatible with third-party timing systems.

* **Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard**



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS




Model 7615 (Outdoor) Football Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 7615	MPC(W)-4/5/6	MPCW-7	MPCX ₂ WIRELESS
TIMING 24" High Intensity Red, Amber, or Translucent White LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59.99. 1/100th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59.99. 1/100th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59.99. 1/100th seconds display during final minute.
TEAM SCORES 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
PERIOD 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
DOWN 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
TIME OUTS LEFT 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
YARDS TO GO 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
BALL ON 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
BALL POSSESSION INDICATORS High Intensity Red, Amber, or Translucent White LED	One for each team shaped in the form of a football.	One for each team shaped in the form of a football.	One for each team shaped in the form of a football.
TIME OF DAY	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	N/A
HORN	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.
JUNCTION BOX	One (1) 4" x 2 1/8" x 2 1/8" with cover, to be installed in dry location (press box), furnished.	N/A	N/A
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) 1/4" diameter. Order length required.	N/A	N/A
SEGMENT TIMING	Supported.	Supported.	Requires MPCX ₂ segment timer control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 24"L x 10' 6"H x 8"D (7.32 x 3.20 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Six (6) brackets provided for mounting. Hanging weight approximately 730 lbs. (331 kg) with ETNs 792 lbs. (359 kg).

CAPTIONS: HOME, GUESTS, PERIOD, BALL ON, DOWN, YDS TO GO, T.O. LEFT, white 15" high. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 4.0 Amps, 50/60 Hz. / 240 VAC, 2.0 Amps, 50/60 Hz.

Requires earth ground.

POWER WITH ETNS (RED/AMBER): 120 VAC, 5.1 Amps, 50/60 Hz. / 240 VAC, 2.6 Amps, 50/60 Hz.

Requires earth ground.

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 6.8 Amps, 50/60 Hz. / 240 VAC, 3.4 Amps, 50/60 Hz.

Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 7.8 Amps, 50/60 Hz. / 240 VAC, 3.9 Amps, 50/60 Hz.

Requires earth ground.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION/

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM