

MAXIMIZE YOUR IMPACT[®]

FULL COLOR INDOOR MESSAGE CENTERS



Many sizes are available. Your local Nevco Display and Scoring Consultant will review all aspects of the project with you, ensuring the correct display type and matrix size is selected.

- Moving messages capture your audience's attention and maximize revenue generation opportunities
- Wired/Wireless control options
- Fast display rate (60 frames per second) ensures graphics and video appear realistic and smooth
- All message centers feature a full matrix design; display graphics and text full screen
- Increased flexibility vs. static signs
- Exceptional viewing angles; display is easily viewed from all directions
- Adapts easily for any installation method
- Unique design for low power consumption

 **NEVCO**
MAXIMIZE YOUR IMPACT[™]

**BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:
WWW.NEVCO.COM**

.....
U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS

10mm True Color

CABINET SIZE	VIEWING MATRIX	NUMBER OF LINES		CHARACTER HEIGHT RANGE		CHARACTERS PER LINE		ACTUAL WEIGHT		MAXIMUM POWER	
		HX W	HXW	Min. Char. Size	Max Char. Size	Min. Char. Size	Max Char. Size	Min. Char. Size	Max Char. Size	Lbs.	Watts
3' x 8'	72 x 240	9	1	2.75"	28"	72	4	110	700	5.8	2.9
3' x 10'	72 x 288	9	1	2.75"	28"	86	5	135	840	7	3.5
4' x 8'	96 x 240	12	1	2.75"	37"	72	3	145	934	7.8	3.9
4' x 10'	96 x 288	12	1	2.75"	37"	86	4	180	1120	9.3	4.7

10mm True Color

PIXEL PITCH	10mm
COLOR	Full 24-bit True Color
COLOR CAPABILITY	68 Billion
DISPLAY ELEMENT	1 SMD LED per pixel
PIXEL BRIGHTNESS	1800 NIT (cd/m ²)
VIEWING ANGLE	170° Horizontal & Vertical
OPERATING TEMP	-40° - 150° F
CONTRAST ENHANCEMENT	N/A
CONTROLLER	Standard Windows based PC or Laptop (not included)
MESSAGE STORAGE	Solid State Flash (no moving parts for high reliability); compressed image format
GRAPHIC CAPABILITIES	Text, animations, logos, multiple fonts, moving messages, corporate advertising, time & temperature, etc
CONTROL SOFTWARE	Nevco Composer™ creation and scheduling software, included with purchase price of each message center
COMMUNICATION OPTIONS	Ethernet Cat5e or Fiber Optic Cable or RF Wireless
POWER	Input: 85 - 265 VAC; Power factor correction for reduced power consumption
DISPLAY DIMMING	64 levels of brightness/auto dimming
DISPLAY CABINET	Reinforced cabinet; weather resistant aluminum
PAINT	Weather resistant with UV inhibitor for long-lasting, durable black finish (PMS by quote)
COMPLIANCE INFORMATION	CUL, UL Listed; FCC, CE Industry Canada
OPERATING ENVIRONMENT	Indoor
GUARANTEE	5 Year limited guarantee

Additional sizes are available. Your local Nevco Display and Scoring Consultant will review all aspects of the project with you, ensuring selection of the correct display type and matrix.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM