



**HOCKEY**

SCOREBOARDS

# MODEL 4-FACE 4710

**Size:** Top: 12'1"sq; Bottom: 9'8" sq; Height: 6' (3.68 x 2.90 x 1.83 meters)

**Approximate hanging weight:** 1,100 lbs. (499 kg)

**Digit Size:** 13"/9" **Digit Color:** High Intensity Red or Amber



OPTIONAL ELECTRONIC TEAM NAMES AVAILABLE

## Advanced timing features ideal for Hockey Facilities.

- Energy-efficient LEDs reduce power consumption and operating expense.
- Ability to retrofit team name caption plates.
- Bright, long lasting LED lamp banks when ordered with rear-lit team names.
- Large, 9" penalty timers included.
- Soccer available with MPC7 series controls.
- Durable and lightweight cabinet design.
- Universal—syncs with Nevco accessories.
- Extended advertising opportunities.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- Built-in Power Factor Correction.

  
**MAXIMIZE YOUR IMPACT™**

**BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:  
 WWW.NEVCO.COM**

**U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360  
 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM**

# INTEGRATED DISPLAY AND SCORING SOLUTIONS



## Model 4-Face 4710 (Indoor) Hockey Scoreboard

### SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 4-FACE 4710	MPC WIRED	MPCW WIRELESS	MPCX <sub>2</sub> WIRELESS
<b>TIMING</b> 13" High Intensity Red LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	N/A
<b>TEAM SCORES</b> 13" Amber LED Digits	Displays 0-99	Displays 0-99	N/A
<b>PERIOD</b> 9" Amber LED Digits	Displays 0-9	Displays 0-9	N/A
<b>PENALTY TIMERS</b> 9" High Intensity Red LED Digits	Displays two for each team. 0:00-9:59	Displays two for each team. 0:00-9:59	N/A
<b>TIME OF DAY</b>	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". "Time of day" can still display after control turned off.	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". "Time of day" can still display after control turned off.	N/A
<b>HORN</b> Two located in scoreboard	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	N/A
<b>JUNCTION BOXES</b>	Two (2) 4"x2 1/8" with covers, furnished per scoreboard for installation.	N/A	N/A
<b>CONTROL CABLE</b>	One (1) length required of 2-WIRE (coaxial type) 1/4" diameter. Order length required.	N/A	N/A
<b>SEGMENT TIMING</b>	Supported.	Supported.	Requires MPCX <sub>2</sub> segment timer control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



**AGENCY APPROVAL:** UL/CUL listed, FCC, CE, INDUSTRY CANADA.

**SCOREBOARD:** Size Top: 12'1"sq; Bottom: 9'8"sq; Height: 6' (3.68 x 2.90 x 1.83 meters). Constructed of aluminum, 4-face structure built from powder coated steel. Lifting and mounting brackets provided at each corner for permanent suspension mounting. Hanging weight approximately 1,100 lbs. (499 kg).

**CAPTIONS (PER FACE):** HOME, GUESTS, PERIOD, PENALTY (2), white 6" high. (HOME and GUESTS are omitted when ordered with ETNs.)

**LED UNITS:** Seven-bar segmented digits with protective aluminum cover.

**POWER WITHOUT ETNS (PER SIDE):** 120 VAC, .66 Amps, 50/60 Hz. / 240 VAC, .33 Amps, 50/60 Hz. Requires earth ground.

**POWER WITH REAR-LIT CAPTIONS (PER SIDE):** 120 VAC, .78 Amps, 50/60 Hz. / 240 VAC, .4 Amps, 50/60 Hz. Requires earth ground.

**POWER WITH ETNS (PER SIDE):** 120 VAC, .87 Amps, 50/60 Hz. / 240 VAC, .44 Amps, 50/60 Hz. Requires earth ground.

**POWER WITH REAR-LIT CAPTIONS AND ETNS (PER SIDE):** 120 VAC, .93 Amps, 50/60 Hz / 240 VAC, .47 Amps, 50/60 Hz. Requires earth ground.

**BUILT-IN LIGHTNING PROTECTION:** All models feature optical isolation circuitry providing additional protection against lightning strikes.

**GUARANTEE:** TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: [NEVCO.COM/WARRANTY-LIMITATION](http://NEVCO.COM/WARRANTY-LIMITATION)

**U.S. SERVICE:** 1-800-851-4040

**INTERNATIONAL SERVICE:** 1-618-664-0360

**CANADA SERVICE:** 1-800-461-8550



MAXIMIZE YOUR IMPACT™

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

[WWW.NEVCO.COM](http://WWW.NEVCO.COM)

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: [INFO@NEVCO.COM](mailto:INFO@NEVCO.COM)