

LACROSSE

SCOREBOARDS

MODEL 5633



Size: 18' x 2' x 8" (5.49 x .61 x .20 meters)

Approximate hanging weight: 120 lbs. (54 kg)

Digit Size: 18" **Digit Color:** High Intensity Red, Amber, or Translucent White



Add on to a Model 5634, 5635, 3680, 3685, 7680 or 7685 for up to 3 Penalty Timers

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.

* **Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard.**



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 5633 (Outdoor) Lacrosse Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 5633	MPC(W)-4/5/6	MPCW-7	MPCX ₂ WIRELESS
PLAYER 18" High Intensity Red, Amber or Translucent White LED Digits	Displays 0-99	Displays 0-99	N/A
PENALTY TIMER 18" High Intensity Red, Amber or Translucent White LED Digits	Two, (1) per team. Any number can be set between 0:00-10:00. DOWN count.	Two, (1) per team. Any number can be set between 0:00-10:00. DOWN count.	N/A
JUNCTION BOX	One (1) 4" x 2 1/8" x 2 1/8" with cover, to be installed in dry location (press box), furnished.	N/A	N/A
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) 3/4" diameter. Order length required.	N/A	N/A
SEGMENT TIMING	Supported.	Supported.	Requires MPCX ₂ segment timer control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 18'L x 2'H x 8"D (5.49 x .61 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Hanging weight approximately 120 lbs. (54 kg).

POWER (RED/AMBER): 120 VAC, 1.3 Amps, 50/60 Hz. / 240 VAC, .6 Amps, 50/60 Hz. Requires earth ground.

POWER (TRANSLUCENT WHITE): 120 VAC, 2.2 Amps, 50/60 Hz. / 240 VAC, 1.1 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM