



SOCCER


SCOREBOARDS

MODEL 1620

Size: 10' x 4' x 8" (3.05 x 1.22 x .20 meters)

Approximate hanging weight: 130 lbs. (60 kg)

Digit Size: 18" **Digit Color:** High Intensity Red, Amber, or Translucent White



Great smaller scoreboard ideal for multi-purpose fields.

- Designed to withstand wind load speed zones exceeding 150 mph.
- Operate wired or wireless.
- Large digits easily seen from long distances.
- White outline striping separates features for greatest readability.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Flexible mounting. Can mount directly to columns OR on laterals for complex or retro-fit installations.
- Flush sign mounting.

* **Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard.**

Combine your scoreboard with a Nevco monochrome or full-color message center to create a complete scoring and display system. Team/Sponsor signs also available.



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM


INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 1620 (Outdoor) Baseball/Softball/Soccer Scoreboard SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 1620	MPC(W)-4/5/6	MPCW WIRELESS	MPCX ₂ WIRELESS
TIMING 18" High Intensity Red, Amber, or Translucent White LED Digits INNING Displays 0-9 instead of time	Displays on two digits. Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. Minutes are displayed until clock reads below one minute, then seconds are displayed. When time is off, time alternately displays minutes and seconds. When the minutes are counting down, the right colon light blinks each second, top right colon light blinks if in first 30 seconds, bottom right colon blinks if in last 30 seconds. Time numerals turn off at :00.	Displays on two digits. Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. Minutes are displayed until clock reads below one minute, then seconds are displayed. When time is off, time alternately displays minutes and seconds. When the minutes are counting down, the right colon light blinks each second, top right colon light blinks if in first 30 seconds, bottom right colon blinks if in last 30 seconds. Time numerals turn off at :00.	Displays on two digits. Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. Minutes are displayed until clock reads below one minute, then seconds are displayed. When time is off, time alternately displays minutes and seconds. When the minutes are counting down, the right colon light blinks each second, top right colon light blinks if in first 30 seconds, bottom right colon blinks if in last 30 seconds. Time numerals turn off at :00.
TEAM SCORES 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99.	Displays 0-99.	Displays 0-99.
INDICATORS 3" Diameter High Intensity Red, Amber, or Translucent White LED cluster	THREE FOR BALL TWO FOR STRIKE TWO FOR OUT	THREE FOR BALL TWO FOR STRIKE TWO FOR OUT (BASEBALL)	THREE FOR BALL TWO FOR STRIKE TWO FOR OUT
PITCH COUNT	N/A	Supported. Integrates with PCD display. Controlled by hand-held switches.	Supported. Integrates with PCD display. Requires Pitch Count MPCX ₂ control.
PITCH TIMER	N/A	Supported. Integrates with 9520 display. Controlled by hand-held switches.	Supported. Integrates with 9520 display. Requires SCD/DGT MPCX ₂ control.
SEGMENT TIMING	Requires MPCW-6 or 7. Controlled by hand-held switches.	Supported. Controlled by hand-held switches.	Supported. Requires Segment Timer MPCX ₂ control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 10'L x 4'H x 8"D (3.05 x 1.22 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Hanging weight approximately 130 lbs. (60 kg).

CAPTIONS: HOME, GUESTS, INN/TIME, BALL, STRIKE, OUT, white letters 8" high.

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

POWER (RED/AMBER): 120 VAC, .8 Amps, 50/60 Hz. / 240 VAC, 0.4 Amps, 50/60 Hz. Requires earth ground.

POWER (TRANSLUCENT WHITE): 120 VAC, 1.5 Amps, 50/60 Hz. / 240 VAC, 0.7 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM



MAXIMIZE YOUR IMPACT®