



SOCCER

SCOREBOARDS

MODEL 1625

Size: 10' x 5' x 8" (3.05 x 1.52 x .20 meters)

Approximate hanging weight: 160 lbs. (73 kg)

Digit Size: 18" **Digit Color:** High Intensity Red or Amber



Scoreboard ideal for Baseball/Softball/Soccer facilities.

- Designed to withstand wind load speed zones exceeding 150 mph.
- Operate wired or wireless.
- Large digits easily seen from long distances.
- White outline striping separates features for greatest readability.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Flexible mounting. Can mount directly to columns OR on laterals for complex or retro-fit installations.
- Flush sign mounting.

Combine your scoreboard with a Nevco monochrome or full-color message center to create a complete scoring and display system. Team/Sponsor signs also available.



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:
WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM


INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 1625 (Outdoor) Baseball/Softball/Soccer Scoreboard SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 1625	MPC(W)-4/5/6	MPCW WIRELESS	MPCX ₂ WIRELESS
TIMING 18" High Intensity Red or Amber LED Digits	Displays on two digits. Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. Minutes are displayed until clock reads below one minute, then seconds are displayed. When time is off, time alternately displays minutes and seconds. When the minutes are counting down, the right colon light blinks each second, top right colon light blinks if in first 30 seconds, bottom right colon blinks if in last 30 seconds. Time numerals turn off at :00.	Displays on two digits. Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. Minutes are displayed until clock reads below one minute, then seconds are displayed. When time is off, time alternately displays minutes and seconds. When the minutes are counting down, the right colon light blinks each second, top right colon light blinks if in first 30 seconds, bottom right colon blinks if in last 30 seconds. Time numerals turn off at :00.	Displays on two digits. Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. Minutes are displayed until clock reads below one minute, then seconds are displayed. When time is off, time alternately displays minutes and seconds. When the minutes are counting down, the right colon light blinks each second, top right colon light blinks if in first 30 seconds, bottom right colon blinks if in last 30 seconds. Time numerals turn off at :00.
TEAM SCORES 18" High Intensity Red or Amber LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
INNING/PERIOD 18" High Intensity Red or Amber LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
INDICATORS 3" diameter High Intensity Red or Amber LED cluster	THREE FOR BALL TWO FOR STRIKE TWO FOR OUT	BASEBALL: THREE FOR BALL TWO FOR STRIKE TWO FOR OUT	BASEBALL: THREE FOR BALL TWO FOR STRIKE TWO FOR OUT
H OR E For hit or error	Displays H or E using the Inning LED unit.	BASEBALL: Displays H or E using the Inning LED unit.	BASEBALL: Displays H or E using the Inning LED unit.
HORN	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. Can sound manually at any time.
PITCH COUNT	N/A	Supported. Integrates with PCD display. Controlled by hand-held switches.	Supported. Integrates with PCD display. Requires Pitch Count MPCX ₂ control.
PITCH TIMER	N/A	Supported. Integrates with 9520 display. Controlled by hand-held switches.	Supported. Integrates with 9520 display. Requires SCD/DGT MPCX ₂ control.
SEGMENT TIMER	Requires MPCW-6 or 7. Controlled by hand-held switches.	Supported. Controlled by hand-held switches.	Supported. Requires Segment Timer MPCX ₂ control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 10'L x 5'H x 8"D (3.05 x 1.52 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Hanging weight approximately 160 lbs. (73 kg).

CAPTIONS: HOME, GUESTS, INNING/PERIOD, TIME, BALL, STRIKE, OUT, white 6" high.

SPONSOR AREA: 3'x2' available sponsorship area.

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

POWER: 120 VAC, 1.1 Amps, 50/60 Hz. / 240 VAC, 0.5 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: WWW.NEVCO.COM/INFO/GUARANTEE.PHP
U.S. SERVICE: 1-800-851-4040. INTERNATIONAL SERVICE: 1-618-664-0360. CANADA SERVICE: 1-800-461-8550.

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM



MAXIMIZE YOUR IMPACT®