




VOLLEYBALL

SCOREBOARDS

MODEL 2710



Size: 8' x 5' x 8" (2.44 x 1.52 x .20 meters)
Approximate hanging weight: 94 lbs. (43 kg)
Digit Size: 13" / 9" **Digit Color:** High Intensity Red & Amber



OPTIONAL ELECTRONIC TEAM NAMES AVAILABLE

Advanced timing features ideal for Volleyball/Wrestling/Basketball Facilities.

- Energy-efficient LEDs reduce power consumption and operating expense.
- Ability to retrofit team name caption plates.
- Bright, long lasting LED lamp banks when ordered with rear-lit team names.
- Large, 4" serve indicator arrows included.
- Durable and lightweight cabinet design.
- Universal—syncs with Nevco accessories.
- Extended advertising opportunities.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- Built-in Power Factor Correction.
- Includes basketball caption plates. Volleyball and wrestling caption plates are optional and can be ordered.
- Soccer available with MPCX₂ and MPC7 series controls.



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS




Model 2710 (Indoor) Volleyball Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES (per face)

MODEL 2710	MPC WIRED	MPCW WIRELESS	MPCX ₂ WIRELESS
TIMING 13" High Intensity Red LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.
TEAM SCORES 13" High Intensity Amber LED Digits	Displays 0-199	Displays 0-199	Displays 0-199
PERIOD 9" High Intensity Amber LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
GAME 9" High Intensity Red LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
WON 9" High Intensity Amber LED Digits	Displays 0-19	Displays 0-19	Displays 0-19
SERVE High Intensity Amber LED	Displays arrow for each team.	Displays arrow for each team.	Displays arrow for each team.
BONUS/DOUBLE BONUS High Intensity Red LED	N/A	N/A	N/A
TIME OF DAY	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". "Time of day" can still display after control turned off.	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". "Time of day" can still display after control turned off.	"Time of day" can display after control turned off.
HORN Two located in scoreboard	Sounds automatically at 0:0 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:0 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:0 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.
JUNCTION BOXES	Two (2) 4" x 2 1/8" x 2 1/8" with covers, furnished per scoreboard for installation.	N/A	N/A
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) 3/4" diameter. Order length required.	N/A	N/A
SEGMENT TIMING	Supported.	Supported.	Requires MPCX ₂ segment timer control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 8'L x 5'H x 8"D (2.44 x 1.5 x .20 meters), constructed of aluminum. Hanging weight approximately 94 lbs. (43 kg).

CAPTIONS: HOME, GUESTS, PERIOD, WON, GAME, white 6" high. B (for bonus) 4" letters. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

POWER WITHOUT ETNS: 120 VAC, .6 Amps, 50/60 Hz. / 240 VAC, .3 Amps, 50/60 Hz. Requires earth ground.

POWER WITH REAR-LIT CAPTIONS: 120 VAC, .73 Amps, 50/60 Hz./ 240 VAC, .37 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS: 120 VAC, .81 Amps, 50/60 Hz / 240 VAC, .41 Amps, 50/60 Hz. Requires earth ground.

POWER WITH REAR-LIT CAPTIONS AND ETNS: 120 VAC, .88 Amps, 50/60 Hz / 240 VAC, .45 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature optical isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM