



WRESTLING

SCOREBOARDS


MODEL 2710



Size: 8' x 5' x 8" (2.44 x .1.52 x .20 meters)


Approximate hanging weight: 110 lbs. (50 kg)

Digit Size: 13"/9" **Digit Color:** Super Bright Red & Amber



Advanced timing features ideal for Wrestling/Volleyball/Basketball Facilities.

- Energy-efficient LEDs reduce power consumption and operating expense.
- Ability to retrofit team name caption plates.
- Bright, long lasting LED lamp banks when ordered with rear-lit team names.
- Large, 4" advantage indicator arrows included.
- Durable and lightweight cabinet design.
- Universal—syncs with Nevco accessories.
- Extended advertising opportunities.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- Built-in Power Factor Correction.
- Includes basketball caption plates. Volleyball and wrestling caption plates are optional and can be ordered.
- Soccer available with MPCX₂ and MPC7 series controls.
- Advantage Timer feature included with wrestling captions.



Combine your scoreboard with a Nevco monochrome or full-color message center to create a complete scoring and display system. Team/Sponsor signs also available.



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 2710 (Indoor) Wrestling Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 2710	MPC WIRED	MPCW WIRELESS	MPCX ₂ WIRELESS
TIMING 13" Super Bright Red LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.
TEAM SCORES 13" Super Bright Amber LED Digits	Displays 0-199	Displays 0-199	Displays 0-199
PERIOD 9" Super Bright Amber LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
WEIGHT 9" Super Bright Red LED Digits	Displays 0-999 or Advantage Time with digital colon.	Displays 0-999 or Advantage Time with digital colon.	Displays 0-999
MATCH 9" Super Bright Amber LED Digits	Displays 0-19	Displays 0-19	Displays 0-19
ADVANTAGE Super Bright Amber LED	Displays arrow for each team.	Displays arrow for each team.	Displays arrow for each team.
BONUS/DOUBLE BONUS Super Bright Red LED	N/A	N/A	N/A
TIME OF DAY	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". "Time of day" can still display after control turned off.	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". "Time of day" can still display after control turned off.	"Time of day" can display after control turned off.
HORN Two located in scoreboard	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.
JUNCTION BOXES	Two (2) 4" x 2 1/8" x 2 1/8" with covers, furnished per scoreboard for installation.	N/A	N/A
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) 3/4" diameter. Order length required.	N/A	N/A
SEGMENT TIMING	Supported.	Supported.	Requires MPCX ₂ segment timer control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 8'L x 5'H x 8"D (2.44 x 1.5 x .20 meters), constructed of aluminum. Hanging weight approximately 71 lbs. (32 kg).

CAPTIONS: HOME, GUESTS, PERIOD, MATCH, WEIGHT, white 6" high. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

POWER WITHOUT ETNS: 120 VAC, .6 Amps, 50/60 Hz. / 240 VAC, .3 Amps, 50/60 Hz. Requires earth ground.

POWER WITH REAR-LIT CAPTIONS: 120 VAC, .73 Amps, 50/60 Hz./ 240 VAC, .37 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS: 120 VAC, .81 Amps, 50/60 Hz / 240 VAC, .41 Amps, 50/60 Hz. Requires earth ground.

POWER WITH REAR-LIT CAPTIONS AND ETNS: 120 VAC, .88 Amps, 50/60 Hz / 240 VAC, .45 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature optical isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: WWW.NEVCO.COM/INFO/GUARANTEE.PHP
U.S. SERVICE: 1-800-851-4040. INTERNATIONAL SERVICE: 1-618-664-0360. CANADA SERVICE: 1-800-461-8550.

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM



MAXIMIZE YOUR IMPACT®